

## P32M



### Manuel Kullanım Özellikli Pnömatik Güçlü Bağlama Elemanları Çift Etkili / Yüksek Torklu

Modüler tasarım  
Kompakt tasarım,  
Yüksek sıkma torklu ve uzun ömürlü.  
Alüminyum gövde  
Sıkma kolları ile farklı kuvvet uygulamaları  
İlave aksesuar olmadan açılma açısının 15°den 135°ye ayar imkanı  
Kilitleme hareket mekanizması  
Ani basınç düşmelerinde, manuel açma özelliği (Emniyetli çalışma)  
Led göstergesi ile indüktif sensör bağlantı özelliği (PLC haberleşme)  
Manuel kullanım özelliği

### Manually operated pneumatic power clamps Double acting / High Torque

Modular design  
Compact design  
High holding torque  
Long life cycle  
Low weight (Aluminium body)  
Wide range of clamping arm variants  
Adjustable opening angle without need for accessory parts 15°.....135°  
Mounting areas at front, back and sides  
Toggle action mechanism  
Manual unlocking in case of pressure drop  
Inductive sensing module with LED display  
Manual use feature



Sipariş No Order No	Sıkma Torku Clamping Moment (Nm)	Tutma Torku Holding Moment (Nm)	g
P32M/63	380	1500	5260

